




Cross port with make up checks

CAVITY: T-16A



sunhydraulics.com/model/IMX



TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Cross port with make up checks
Mounting Hole Diameter	10,7 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2
Open Cavities	2
Cavity	T-16A
Port Size	1" BSPP
Model Weight	9.06 kg.

CONFIGURATION

/S Modifier 65-45-12 Ductile Iron, Buna-N, Blackened

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

INCLUDED COMPONENTS

Modifiers	Ports
IMX, /V	All Ports: 1" BSPP;

Part	Description	Quantity
CXHAXAN	Cartridge	2

CONFIGURATION OPTIONS Model Code Example: IMX/S

MODIFIER (/S)

/S 65-45-12 Ductile Iron, Buna-N, Blackened

6061-T651 Aluminum, Buna-N

V 6061-T651 Aluminum, Viton

Y 65-45-12 Ductile Iron, Viton, Blackened

© 2019 Sun Hydraulics